

What is claimed is:

5 1. An implantable cable for transmission of a signal to and from a body tissue of a vertebrate, comprising:

 a fiber optic bundle having a surface of non-immunogenic, physiologically compatible material, said fiber optic bundle being capable of being permanently implanted in a body cavity or subcutaneously, said fiber optic bundle having a distal end for implantation at or adjacent to the
10 body tissue and a proximal end;

 said proximal end being adapted to be coupled to and direct an optical signal source;

 said distal end being adapted to be coupled to an optical stimulator;

15 said fiber optic bundle delivering an optical signal intended to cause an optical stimulator coupled to said distal end to deliver an excitatory stimulus to a selected body tissue, the stimulus being causing the selected body tissue to function as desired.

20 2. The implantable cable as claimed in claim 1, wherein said distal end is adapted to be coupled to a sensor.

 3. The implantable cable as claimed in claim 2, wherein said fiber optic bundle delivering an optical signal from a coupled sensor to said
25 proximal end.

 4. The implantable cable as claimed in claim 1, further comprising:

a photoresponsive device for converting the light transmitted by said fiber optic bundle into electrical energy, and for sensing variations in the light energy to produce control signals;

a charge accumulating device for receiving and storing the electrical energy produced by the photoresponsive device; and

a discharge control device, responsive to the control signals, for directing the stored electrical energy from the charge accumulating device to a cardiac assist device associated with a heart.

5. The implantable cable as claimed in claim 4, wherein said photoresponsive device is a small surface area photodiode and a large surface area photodiode, said small surface area photodiode sensing variations in the light energy to produce control signals, said large surface area photodiode converting the light transmitted by said photonic lead system into electrical energy.

6. The implantable cable as claimed in claim 4, wherein said photoresponsive device is an array of photodiodes having a first section of photodiodes and a second section of photodiodes, said first section of photodiodes sensing variations in the light energy to produce control signals, said second section of photodiodes converting the light transmitted by said photonic lead system into electrical energy.

7. The implantable cable as claimed in claim 4, wherein said photoresponsive device includes a charge transfer control circuit and a photodiode, said charge transfer control circuit controlling a discharging of a

photodiode capacitance in two separate discharge periods during an integration period of the photodiode such that a first discharge period of the photodiode capacitance provides the sensing of variations in the light energy to produce control signals and a second discharge period of the photodiode capacitance provides the converting the light transmitted by said photonic lead system into electrical energy.

8. The implantable cable as claimed in claim 7, wherein the first discharge period is completed before the second discharge period.

9. The implantable cable as claimed in claim 7, wherein the first discharge period is a shorter time duration than the time duration of the second discharge period.

10. The implantable cable as claimed in claim 7, wherein the integration period corresponds to the sampling period of the light to derive control data.

11. The implantable cable as claimed in claim 7, wherein during the first discharge period, a control signal sensing circuit is connected to said photodiode, and during the second discharge period, said charge accumulating device is connected to said photodiode.

12. The implantable cable as claimed in claim 4, wherein said charge accumulating device is a capacitor.

13. The implantable cable as claimed in claim 4, wherein said charge accumulating device is a rechargeable battery.

14. The implantable cable as claimed in claim 4, wherein said
5 discharge control device is a controllable switch.

15. An implantable cable for transmission of a signal to and from a body tissue of a vertebrate, comprising:

1007888-021902
10 a fiber optic bundle having a surface of non-immunogenic, physiologically compatible material, said fiber optic bundle being capable of being permanently implanted in a body cavity or subcutaneously, said fiber optic bundle having a distal end for implantation at or adjacent to the body tissue and a proximal end;

15 said proximal end being adapted to be coupled to an optical signal receiver;

said distal end being adapted to be coupled to a sensor;

said fiber optic bundle delivering an optical signal from a coupled sensor intended to cause an optical signal receiver coupled to said proximal
20 end to monitor characteristics of a selected body tissue.

16. An implantable cable for the transmission of power to a body tissue of a vertebrate, comprising:

25 a fiber optic lead having a surface of non-immunogenic, physiologically compatible material and being capable of being permanently implanted in a body cavity or subcutaneously;

said fiber optic lead having,

a proximal end being adapted to be coupled to an optical portal,
a coupled optical portal being able to receive light from a source
external to the vertebrate, and

a distal end being adapted to be coupled to a photoelectric
receiver, a coupled photoelectric receiver being able to convert light
into electrical energy for use at said distal end.

17. The implantable cable as claimed in claim 16, wherein said distal
end is adapted to be coupled to a sensor.

18. The implantable cable as claimed in claim 17, wherein said fiber
optic lead delivering an optical signal from a coupled sensor to said
proximal end.

19 22. The implantable cable as claimed in claim 16, further comprising:
a photoresponsive device for converting the light transmitted by said
fiber optic lead into electrical energy, and for sensing variations in the light
energy to produce control signals;

a charge accumulating device for receiving and storing the electrical
energy produced by the photoresponsive device; and

a discharge control device, responsive to the control signals, for
directing the stored electrical energy from the charge accumulating device to
a cardiac assist device associated with a heart.

10 23. The implantable cable as claimed in claim ¹⁹22, wherein said
photoresponsive device is a small surface area photodiode and a large
surface area photodiode, said small surface area photodiode sensing
variations in the light energy to produce control signals, said large surface
5 area photodiode converting the light transmitted by said photonic lead
system into electrical energy.

1007655-02302 10 a1 24. The implantable cable as claimed in claim ¹⁹22, wherein said
photoresponsive device is an array of photodiodes having a first section of
photodiodes and a second section of photodiodes, said first section of
photodiodes sensing variations in the light energy to produce control signals,
said second section of photodiodes converting the light transmitted by said
photonic lead system into electrical energy.

15 a2 25. The implantable cable as claimed in claim ¹⁹22, wherein said
photoresponsive device includes a charge transfer control circuit and a
photodiode, said charge transfer control circuit controlling a discharging of a
photodiode capacitance in two separate discharge periods during an
integration period of the photodiode such that a first discharge period of the
20 photodiode capacitance provides the sensing of variations in the light energy
to produce control signals and a second discharge period of the photodiode
capacitance provides the converting the light transmitted by said photonic
lead system into electrical energy.

25 a3 26. The implantable cable as claimed in claim ²²25, wherein the first
discharge period is completed before the second discharge period.

27. The implantable cable as claimed in claim ²²25, wherein the first discharge period is a shorter time duration than the time duration of the second discharge period.

28. The implantable cable as claimed in claim ²²25, wherein the integration period corresponds to the sampling period of the light to derive control data.

29. The implantable cable as claimed in claim ²²25, wherein during the first discharge period, a control signal sensing circuit is connected to said photodiode, and during the second discharge period, said charge accumulating device is connected to said photodiode.

30. The implantable cable as claimed in claim ¹⁹22, wherein said charge accumulating device is a capacitor.

31. The implantable cable as claimed in claim ¹⁹22, wherein said charge accumulating device is a rechargeable battery.

32. The implantable cable as claimed in claim ¹⁹22, wherein said discharge control device is a controllable switch.

33. An implantable cable for the transmission of power to a body tissue of a vertebrate, comprising:

a fiber optic lead having a surface of non-immunogenic, physiologically compatible material and being capable of being permanently implanted in a body cavity or subcutaneously;

said fiber optic lead having,

a distal end being adapted to be coupled to a sensor, a coupled sensor being able to produce a light signal based on a measured characteristic of a selected body tissue region, and

a proximal end being adapted to be coupled to an optical portal, said optical portal being able to receive light produced by a coupled sensor.

34. An implantable cable for the transmission of power to a body tissue of a vertebrate, comprising:

a fiber optic lead having a surface of non-immunogenic, physiologically compatible material and being capable of being permanently implanted in a body cavity or subcutaneously;

said fiber optic lead having,

a proximal end being adapted to be coupled to an optical portal, a coupled optical portal being able to receive light from a light source, and

a distal end being adapted to be coupled to a photoelectric receiver, a coupled photoelectric receiver being able to convert light into electrical energy for use at said distal end.

35. The implantable cable as claimed in claim 34, wherein said distal end is adapted to be coupled to a sensor.

33 36. The implantable cable as claimed in claim ³²35, wherein said fiber optic lead delivering an optical signal from a coupled sensor to said proximal end.

5 34 37. The implantable cable as claimed in claim ³¹34, further comprising:
a photoresponsive device for converting the light transmitted by said fiber optic lead into electrical energy, and for sensing variations in the light energy to produce control signals;

10 a charge accumulating device for receiving and storing the electrical energy produced by the photoresponsive device; and

a discharge control device, responsive to the control signals, for directing the stored electrical energy from the charge accumulating device to a cardiac assist device associated with a heart.

15 35 38. The implantable cable as claimed in claim ³⁴37, wherein said photoresponsive device is a small surface area photodiode and a large surface area photodiode, said small surface area photodiode sensing variations in the light energy to produce control signals, said large surface area photodiode converting the light transmitted by said photonic lead system into electrical energy.

20 36 39. The implantable cable as claimed in claim ³⁴37, wherein said photoresponsive device is an array of photodiodes having a first section of photodiodes and a second section of photodiodes, said first section of photodiodes sensing variations in the light energy to produce control signals,

said second section of photodiodes converting the light transmitted by said photonic lead system into electrical energy.

37 40. The implantable cable as claimed in claim ³⁷37, wherein said
5 photoresponsive device includes a charge transfer control circuit and a
photodiode, said charge transfer control circuit controlling a discharging of a
photodiode capacitance in two separate discharge periods during an
integration period of the photodiode such that a first discharge period of the
photodiode capacitance provides the sensing of variations in the light energy
10 to produce control signals and a second discharge period of the photodiode
capacitance provides the converting the light transmitted by said photonic
lead system into electrical energy.

37 41. The implantable cable as claimed in claim ³⁷40, wherein the first
15 discharge period is completed before the second discharge period.

37 42. The implantable cable as claimed in claim ³⁷40, wherein the first
discharge period is a shorter time duration than the time duration of the
second discharge period.

40 43. The implantable cable as claimed in claim ³⁷40, wherein the
20 integration period corresponds to the sampling period of the light to derive
control data.

41 44. The implantable cable as claimed in claim ³⁷40, wherein during the
25 first discharge period, a control signal sensing circuit is connected to said

photodiode, and during the second discharge period, said charge accumulating device is connected to said photodiode.

5 ⁴²45. The implantable cable as claimed in claim ³⁴37, wherein said charge accumulating device is a capacitor.

⁴³46. The implantable cable as claimed in claim ³⁴37, wherein said charge accumulating device is a rechargeable battery.

10 ⁴⁴47. The implantable cable as claimed in claim ³⁴37, wherein said discharge control device is a controllable switch.

⁴⁵48. An implantable cable for the transmission of power to a body tissue of a vertebrate, comprising:

15 a fiber optic lead having a cylindrical surface of non-immunogenic, physiologically compatible material and being capable of being permanently implanted in a body cavity or subcutaneously;

said fiber optic lead having,

20 a proximal end coupled to an electro-optical source, said electro-optical source converting electrical energy into light energy, and

a distal end coupled to a photoelectric receiver, said photoelectric receiver converting light energy into electrical energy for use at said distal end.

25 ⁴⁶49. The implantable cable as claimed in claim ⁴⁵48, further comprising:

a photoresponsive device for converting the light transmitted by said fiber optic lead into electrical energy, and for sensing variations in the light energy to produce control signals;

a charge accumulating device for receiving and storing the electrical energy produced by the photoresponsive device; and

a discharge control device, responsive to the control signals, for directing the stored electrical energy from the charge accumulating device to a cardiac assist device associated with a heart.

10075550-027902
10 47 50. The implantable cable as claimed in claim 46, wherein said photoresponsive device is a small surface area photodiode and a large surface area photodiode, said small surface area photodiode sensing variations in the light energy to produce control signals, said large surface area photodiode converting the light transmitted by said photonic lead system into electrical energy.
15

48 51. The implantable cable as claimed in claim 46, wherein said photoresponsive device is an array of photodiodes having a first section of photodiodes and a second section of photodiodes, said first section of photodiodes sensing variations in the light energy to produce control signals, said second section of photodiodes converting the light transmitted by said photonic lead system into electrical energy.
20

49 52. The implantable cable as claimed in claim 46, wherein said photoresponsive device includes a charge transfer control circuit and a photodiode, said charge transfer control circuit controlling a discharging of a
25

photodiode capacitance in two separate discharge periods during an integration period of the photodiode such that a first discharge period of the photodiode capacitance provides the sensing of variations in the light energy to produce control signals and a second discharge period of the photodiode capacitance provides the converting the light transmitted by said photonic lead system into electrical energy.

1007888 "021902
100
10
49
§3. The implantable cable as claimed in claim 52, wherein the first discharge period is completed before the second discharge period.

49
§4. The implantable cable as claimed in claim 52, wherein the first discharge period is a shorter time duration than the time duration of the second discharge period.

15
49
§5. The implantable cable as claimed in claim 52, wherein the integration period corresponds to the sampling period of the light to derive control data.

49
20
§6. The implantable cable as claimed in claim 52, wherein during the first discharge period, a control signal sensing circuit is connected to said photodiode, and during the second discharge period, said charge accumulating device is connected to said photodiode.

46
25
§7. The implantable cable as claimed in claim 49, wherein said charge accumulating device is a capacitor.

⁴⁶
55 58. The implantable cable as claimed in claim ⁴⁶49, wherein said charge
accumulating device is a rechargeable battery.

⁴⁶
5 59. The implantable cable as claimed in claim ⁴⁶49, wherein said
discharge control device is a controllable switch.

1007888 021902